Massachusetts Institute of Technology Instrumentation Laboratory Cambridge, Massachusetts

## JUL 3 1968

DANCE Memo #76

To:

Distribution

From:

N. Fisher

Date:

18 June 1968

Subject: Comparison of Radar Scale Factors in SUNDANCE and GSOP

Table I and Table II below contain respectively the radar scale factors suggested for inclusion in SUNDANCE by L. J. Johnson in a memorandum dated 12/1/67 and the actual radar scale factors in SUNDANCE. It should be noted that the recommended scale factors for the LR range and the actual ones are different.

TABLE I (GSOP)				
Equipment	Parameter	Bias Count	Factor	
LR	V <sub>XA</sub> scale factor	12, 288. 2	-0.6440 ft/sec/count	
LR	V <sub>YA</sub> scale factor	12, 288. 2	1.212 ft/sec/count	
LR	V <sub>ZA</sub> scale factor	12, 288. 2	0.8668 ft/sec/count	
LR	Range, low scale factor	none	1:079 ft/count	
LR	Range, high scale factor	none	5.395 ft/count = (5)(1.079)	
RR	Range rate	17,000	-0.6278	
RR	Range, low scale	none	9.38 ft/count	
RR	Range, high scale	none	75.04 ft/count = (8)(9.38)	

## TABLE II (SUNDANCE)

quipment	Parameter	Bias Count	Factor
LR	V <sub>XA</sub> scale factor	12, 288. 2	-0.6440 ft/sec/count
LR	V <sub>YA</sub> scale factor	12, 288. 2	1.212 ft/sec/count
LR	VZA scale factor	12, 288. 2	0.8668 ft/sec/count
LR	Range, low scale factor	none	1.0795 ft/count
LR	Range, high scale factor	none	(4.9977)(1.0795) ft/count = 5.39501715 *
RR	Range rate	17,000	-0.6278
RR	Range, low scale factor	none	9.38 ft/count
RR	Range, high scale factor	none	75.04 ft/count = (8)(9.38) **

The range is multiplied by 4.9977 and is then multiplied by the low scale factor in Pinball.

<sup>\*\*</sup> The range is multiplied by 8 and is then multiplied by the low scale factor in Pinball.