

An ontology of resources for Linked Data

Harry Halpin and **Valentina Presutti**

LDOW @ WWW2009 - Madrid, April 20th

Outline

- Premises and background
- Proposal overview
- Some details of IRW ontology
- Simple application in the LOD context
- Next steps

Premises

- General issue on identity and reference on the Web
 - We want to “handle” things that are not *web accessible*
- Practical issues in applications such as LOD
 - use of owl:sameAs, less contradictions, ...
- We need a solution that goes beyond solving the current urgent issues, but it has to be easy
- Is there a low hanging fruit?
 - A lightweight ontology with Web and SW architecture core concepts and relations → IRW
 - Aligned modules for each specific application such as LOD → lod2irw
- Immediate benefit
 - We will argue by referring to one model i.e. IRW
 - means we have agreed on at least few things
 - Existing applications such as LOD can take immediate actions
 - E.g. self-describing resources in LOD


The background

- The problem of identity and reference on the web has been discussed for long in Web circles and outside them
 - E.g., TAG related awsw is very active on this topic
- Standard documents
 - W3C TAG, RFC 2396, HTTP RFC, URI RFC 3986, IETF RFC
- Scientific literature
 - I3 workshop series, IJSWIS 4(2), etc..
- Notes and mailing list archives
 - E.g. TimBL's "Generic Resource", awsw ml archive etc.
- Ontologies
 - RDFS, DUL + IOL, LMM, IRE, GEN...
- Projects and initiatives
 - OKKAM, LOD, etc..


Towards a solution

- A simple *hub* OWL ontology
- Identity and Reference on the Web (IRW)
- Only few core concepts and relations
 - For the core concepts and relations we took practices from DUL+IOL, LMM and IRE
- Specific applications such as LOD have their small ontology that reuses IRW, if needed
 - “...many small ontological components largely created of pointers to each other...”
- Result
 - a network of ontologies for describing resources involved in applications on the web
- Why?
 - It can be used in applications such as LOD, over the Web
 - It helps the debate...

From recent awwsw discussion



IRW and specific modules




IRW Ingredients

- Identification and Reference
- Resources and their types
- Access and Redirection
- “Hypertext” Web transaction
and
- LOD transaction


Identification and Reference

- A class for URIs allows us to talk about different types of URIs
- `irw:identifies`
 - Functional
 - The owner of the URI intends to identify a certain thing
- `irw:refersTo`
 - A URI refers to whatever results from its usage on the (Semantic) Web
 - Complies with *logicians' position*: the referent of a URI is ambiguous
- `irw:identifies` `rdfs:subPropertyOf` `irw:refersTo`




Resource types

- irw:Resource
 - is meant to express the same intuition as rdfs:Resource
 - In a possible OWL-full IRW it would be owl:equivalentTo rdfs:Resource
 - Two disjoint subclasses
 - IR
 - nIR




Resource types

- IR:
 - a resource which has the property that all of its essential characteristics can be conveyed in a message
 - i.e. TAG IR
 - E.g. the wikipedia text describing Rome
 - is about something
 - E.g. about Rome the place
 - is realized by some “information realization”
 - e.g., the web representation on the wikipedia server of the page describing Rome




Resource types

- **WebRepresentation**
 - The realization of a message encoding that *goes on the wire*, according to an interaction protocol (e.g. http), in order to resolve a Web-accessible resource
- **WebResource**
 - A special kind of IR
 - It has at least a web representation
 - It is identified by at least one URI



Resource types


- nIR: the complement of IR
 - Three subclasses help to give the intuition of what is an IR and what is a nIR
 - Non-normative modeling
 - There are many other plausible distinctions
 - Physical entities
 - A *touchable* resource
 - E.g. physical people, artifacts, places, etc.
 - Conceptual resources
 - They exist in the social communication process
 - E.g. legal entities, political entities, etc.
 - Abstract resources
 - Abstract things, combinatorial spaces. They cannot be located in space-time
 - E.g. functions, the infinite set of names that can be defined in a namespace, etc.



What a name!


Access and Redirection

- **irw:accesses**
 - Transitive
 - A URI allows access to the thing it identifies/refers to
 - The notion of access is broader than that of web access
- **irw:redirectsTo**
 - `rdfs:subPropertyOf irw:accesses`
 - a URI can redirect to another URI e.g. http 303 redirect
 - The destination URI must identify a resource that is associated with a web representation
 - Two subproperties in a “tag –specific module”
 - `tag2irw:redirects303To`
 - `tag2irw:redirectsHashTo`
- **irw:SemanticWebURI**
 - Must have at least one redirect
 - identify nIR



“Hypertext” Web transactions

- irw:WebClient
 - A client in the Web context
- irw:requests
 - Is a hook to the HTTP in RDF
- irw:WebServer
 - A server hosting web representations
- irw:isResolutionOf
 - Inverse of irw:resolvesTo which is currently implemented by mapping a URI to an IP
- irw:isLocationOf
 - the Web server concretely can respond to an HTTP request with a particular Web representation



Self-describing linked data

- tag2http:redirects303To is ambiguous re the type of resource identified
 - It can occur between two IRs
 - The resource can embed the following in order to self describe itself and become *LOD-enabled*



```
dbpedia:resource/Eiffel_Tower rdf:type irw:NonInformationResource (*)
```


- From last Vocamp in Ibiza: can we avoid 303, then?

(*) dbpedia: <http://dbpedia.org/>

Linked Data Transaction

- In the `ldow2irw` sample module we have defined the class `ldow:AssociatedDescription`
 - It is an `InformationResource`
 - It is about at least one `NonInformationResource` whose URI redirects to its one

```
dbpedia:resource/Eiffel_Tower rdf:type irw:NonInformationResource
dbpedia:resource/Eiffel_Tower irw:redirects303To dbpedia:data/Eiffel_Tower
dbpedia:data/Eiffel_Tower rdf:type ldow:AssociatedDescription
→
dbpedia:data/Eiffel_Tower rdf:type irw:InformationResource
```

An orange oval with a gradient and a drop shadow, containing the text "ldow2irw".

ldow2irw

A simple example of application

Semantic Validation of Linked Data ...with very simple reasoning

INPUT → http://dbpedia.org/resource/Eiffel_Tower

Check

1. If HTTP 303 Request with content request type "application/rdf+xml" returns a RDF file
2. If HTTP 303 Request with content request type "text/html" returns a HTML file

OUTPUT (if succeeded) →

http://dbpedia.org/resource/Eiffel_Tower rdf:type irw:NonInformationResource

http://dbpedia.org/data/Eiffel_Tower rdf:type ldow:AssociatedDescription

http://dbpedia.org/page/Eiffel_Tower rdf:type ldow:AssociatedDescription

http://dbpedia.org/resource/Eiffel_Tower ldow:redirects303To http://dbpedia.org/page/Eiffel_Tower

http://dbpedia.org/resource/Eiffel_Tower ldow:redirects303To http://dbpedia.org/data/Eiffel_Tower

SOME ADDITIONAL ANNOTATIONS CAN BE ADDED:

http://dbpedia.org/data/Eiffel_Tower irw:about http://dbpedia.org/resource/Eiffel_Tower

http://dbpedia.org/page/Eiffel_Tower irw:about http://dbpedia.org/resource/Eiffel_Tower

...

→ Also useful for detecting possible misuses of owl:sameAs

What next?

- To fix/refine IRW based on awwsw discussions/inputs as well as from practical experiences such as those presented today
 - Domain-specific applications can link to IRW as a shared *meta-level* vocabulary
- To align IRE to “Generic Resource” ontology
- Implementations
 - E.g. the ongoing IKS project, SMW extension, etc.

Questions?

