


IBM



AS - 205 Instrument Unit Model Specification

(“As Specified” Systems)

IBM No. 65-256-0005H

1 December 1965

**Huntsville Facility
Space Guidance Center**



WARNING

The data contained in this document has been developed from deductions against the Component Specifications of the Saturn Instrument Unit.


This data may be pessimistic or optimistic, depending on the quality of the MSFC/IBM Specifications.

Because the IU is presently "built to print", not to Specification, this data must not be treated as a complete representation of total IU performance.


Every caution must be taken that this data not be misinterpreted, by either MSFC/NASA or IBM personnel.

Therefore, it may not be reproduced without the written permission of IBM Systems Engineering,

D208.



R. T. Smith



S. J. Dudek
Approved by S. J. Dudek

12/1/65

TABLE OF CONTENTS

Section	Title	Page
1	SCOPE	1-1
	1.1 Purpose	1-1
	1.2 Objective	1-1
	1.3 Authority	1-1
	1.4 Performance.	1-2
2	APPLICABLE DOCUMENTS.	2-1
	2.1 Specifications, Standards, and Processes	2-1
3	CONFIGURATION	3-1
	3.1 Stage Function	3-1
	3.2 General Description.	3-1
	3.3 External Configuration	3-1
	3.4 Internal Configuration.	3-4
	3.5 Mass Characteristics	3-4
	3.6 Interface Control	3-4
4	SYSTEM PERFORMANCE.	4-1
	4.1 Instrument Unit Performance.	4-1
	4.2 Instrument Unit System Performance.	4-3
	4.2.1 Guidance System.	4-23
	4.2.1.1 Function	4-23
	4.2.1.2 Configuration	4-23
	4.2.1.2.1 Applicable Documents	4-23
	4.2.1.2.3 Description	4-26
	4.2.1.3.1 Guidance Reference Release	4-26
	4.2.1.3.2 Liftoff	4-26
	4.2.1.3.3 S-IB Burn	4-26
	4.2.1.3.4 S-IVB Burn	4-29
	4.2.1.3.5 Orbital Guidance	4-29
	4.2.1.3.6 Interfaces	4-29
	4.2.1.4 Performance	4-29
	4.2.1.4.1 Performance Characteristics	4-30
	4.2.1.4.2 Methods and Conditions for Performance Parameter Determination	4-61
	4.2.1.5 Inertial Subsystem	4-64
	4.2.1.5.1 Function	4-64
	4.2.1.5.2 Configuration	4-64
	4.2.1.5.3 Description	4-66
	4.2.1.5.4 Interfaces	4-74
	4.2.1.5.5 Performance	4-74

TABLE OF CONTENTS (Continued)

Section	Title	Page
4.2.1.6	Computer Subsystem	4-77
4.2.1.6.1	Function	4-77
4.2.1.6.2	Configuration	4-78
4.2.1.6.3	Description	4-78
4.2.2	Attitude Control System	4-93
4.2.2.1	Function	4-93
4.2.2.2	Configuration	4-93
4.2.2.2.1	Attitude Control System Block Diagram	4-93
4.2.2.2.2	Component Listing.	4-95
4.2.2.3	Description	4-95
4.2.2.3.1	Attitude Control System Flow Diagram Description	4-95
4.2.2.4	Interfaces	4-108
4.2.2.5	Performance	4-108
4.2.3	Sequencing System.	4-113
4.2.3.1	Function	4-113
4.2.3.2	Configuration	4-113
4.2.3.2.1	Applicable Documents	4-115
4.2.3.3	Description	4-115
4.2.3.3.1	Discrete Function Sequencing	4-115
4.2.3.3.2	Electrical Interface: External to Instrument Unit	4-124
4.2.3.4	Performance.	4-133
4.2.3.4.1	Discrete Issue Timing.	4-134
4.2.3.4.2	Discrete Interpretation Time	4-134
4.2.3.4.3	Sequencing System, Manned or Unmanned Mission.	4-134
4.2.4	Instrumentation System	4-135
4.2.4.1	Function	4-135
4.2.4.2	Configuration	4-135
4.2.4.3	Description	4-141
4.2.4.3.1	System Flow Diagram.	4-141
4.2.4.3.2	Instrument Unit Interfaces	4-142
4.2.4.4	Characteristics	4-145
4.2.4.4.1	Detail Performance.	4-145
4.2.4.4.2	Environmental Requirements	4-147
4.2.4.4.3	Calibration.	4-149
4.2.4.4.4	Physical Requirements	4-150
4.2.4.4.5	Components and Minor Subsystems	4-157
4.2.5	Tracking System	4-191
4.2.5.1	Function	4-191
4.2.5.2	Configuration	4-191
4.2.5.3	Performance.	4-191
4.2.5.4	Subsystem Description	4-191
4.2.5.4.1	AZUSA Subsystem.	4-191
4.2.5.4.2	C-Band Transponder Subsystem	4-197
4.2.6	Command System	4-205
4.2.6.1	Function	4-205

TABLE OF CONTENTS (Continued)

Section	Title	Page
4.2.6.2	Configuration	4-205
4.2.6.2.1	Description	4-205
4.2.6.2.2	Applicable Documents	4-211
4.2.6.3	Description	4-212
4.2.6.3.1	Command System Flow Diagram	4-212
4.2.6.3.2	Instrument Unit Interfaces	4-212
4.2.6.4	Performance.	4-212
4.2.6.4.1	System Performance	4-212
4.2.6.4.2	Time Table For Data	4-217
4.2.7	Electrical System	4-219
4.2.7.1	Function	4-219
4.2.7.2	Configuration	4-219
4.2.7.2.2	Applicable Documents	4-219
4.2.7.3	Electrical System Description	4-219
4.2.7.3.1	Vehicle Electrical System Description	4-219
4.2.7.3.2	Instrument Unit Electrical System Description	4-220
4.2.7.3.3	Grounding	4-225
4.2.7.3.4	Interface	4-225
4.2.7.3.5	Performance	4-229
4.2.8	Emergency Detection System	4-231
4.2.8.1	Function	4-231
4.2.8.2	Configuration	4-231
4.2.8.2.1	Description	4-231
4.2.8.2.2	Applicable Documents	4-233
4.2.8.3	Description	4-233
4.2.8.3.1	System Functional Flow	4-233
4.2.8.3.2	Electrical Interface: External to Instrument Unit	4-242
4.2.8.4	Performance.	4-255
4.2.8.4.1	Automatic Abort	4-255
4.2.8.4.2	Manual Abort	4-256
4.2.8.4.3	Input and Output Voltage.	4-256
4.2.9	Environmental Control System	4-257
4.2.9.1	Function	4-257
4.2.9.2	Configuration	4-257
4.2.9.2.1	Block Diagram Description	4-257
4.2.9.2.2	Applicable Documents	4-257
4.2.9.3	Description	4-257
4.2.9.3.1	System Flow Diagrams	4-257
4.2.9.3.2	ECS/IU Interfaces	4-257
4.2.9.4	Performance.	4-259
4.2.9.4.1	Detailed Performance Characteristics	4-259
4.2.9.4.2	Subsystems of the Environmental Control System	4-259
4.2.10	Structural System	4-273
4.2.10.1	Function	4-273
4.2.10.2	Configuration	4-273

TABLE OF CONTENTS (Continued)

Section	Title	Page
	4.2.10.2.1 Block Diagram	4-273
	4.2.10.2.2 Applicable Documents	4-273
	4.2.10.3 Description	4-273
	4.2.10.3.1 Flow Diagram	4-273
	4.2.10.3.2 Interfaces	4-277
	4.2.10.4 Performance	4-278
	4.2.10.4.1 Detailed Performance Characteristics	4-278
5	COMPONENT DESCRIPTIONS.	5-1
	5.1 Guidance System	5-3
	5.1.1 ST-124M Inertial Platform Assembly.	5-3
	5.1.1.1 Function of Hardware	5-3
	5.1.1.2 Configuration	5-3
	5.1.1.3 Interface	5-6
	5.1.1.4 Functional Characteristics	5-7
	5.1.1.5 Component Characteristics	5-9
	5.1.1.6 Sequencing	5-17
	5.1.2 ST-124M Platform Electronic Assembly	5-17
	5.1.2.1 Function of Hardware	5-17
	5.1.2.2 Configuration	5-17
	5.1.2.3 Operation	5-18
	5.1.2.4 Interfaces	5-18
	5.1.2.5 Performance Characteristics	5-18
	5.1.3 Platform AC Power Supply	5-21
	5.1.3.1 Function of Hardware	5-21
	5.1.3.2 Performance	5-21
	5.1.3.3 Functional Characteristics	5-21
	5.1.4 Accelerometer Signal Conditioner	5-23
	5.1.4.1 Function of Hardware	5-23
	5.1.4.2 Configuration	5-23
	5.1.4.3 Performance	5-23
	5.1.4.4 Functional Characteristics	5-24
	5.1.5 Launch Vehicle Digital Computer	5-25
	5.1.5.1 Function of Hardware	5-25
	5.1.5.2 Functional Requirements	5-29
	5.1.5.3 Configuration	5-31
	5.1.5.3.1 Input-Output Requirements	5-31
	5.1.5.3.2 Functional Organization	5-32
	5.1.5.3.3 Interface	5-38
	5.1.5.3.4 Reliability	5-38
	5.1.6 Launch Vehicle Data Adapter	5-38
	5.1.6.1 Function of Hardware	5-38
	5.1.6.1.1 Physical Description	5-39
	5.1.6.2 Functional Requirements	5-39

TABLE OF CONTENTS (Continued)

Section	Title	Page
5.1.6.2.1	Input/Output Requirements	5-40
5.1.6.2.2	Guidance and Control	5-41
5.1.6.2.3	Computer Controls	5-41
5.1.6.2.4	Discrete Outputs.	5-42
5.1.6.2.5	Discrete Inputs	5-42
5.1.6.2.6	Telemetry	5-43
5.1.6.3	Functional Organization.	5-43
5.1.6.3.1	Power Supplies and Power Control	5-43
5.1.6.3.2	Timing Generator	5-44
5.1.6.3.3	Address Decoder	5-44
5.1.6.3.4	Frequency Generator	5-44
5.1.6.3.5	Input Data Handling	5-44
5.1.6.3.6	Output	5-51
5.1.6.4	Performance	5-56
5.1.6.5	Reliability	5-67
5.1.6.5.1	Triple Modular Redundancy.	5-67
5.2	Attitude Control System.	5-69
5.2.1	Flight Control Computer	5-69
5.2.1.1	Function of Hardware	5-69
5.2.1.2	Performance.	5-70
5.2.1.2.1	First Stage Powered Flight	5-70
5.2.1.2.2	Second Stage Powered Flight	5-70
5.2.1.2.3	Coast Flight	5-71
5.2.1.3	Functional Characteristics	5-71
5.2.2	Control Signal Processor	5-76
5.2.2.1	Function of Hardware	5-76
5.2.2.2	Performance	5-77
5.2.2.3	Functional Characteristics	5-77
5.2.3	Control Accelerometers (Yaw and Pitch).	5-79
5.2.3.1	Function of Hardware	5-79
5.2.3.2	Performance	5-80
5.2.3.3	Functional Characteristics	5-80
5.3	Sequencing System	5-83
5.3.1	Switch Selector Model II.	5-83
5.3.1.1	Procurement Specification 6009026 Function of Hardware	5-83
5.3.1.2	Physical Characteristics	5-84
5.3.2	Control Distributor	5-85
5.3.2.1	Procurement Specification 40M39521A Function of Hardware	5-85
5.3.2.2	Physical Characteristics	5-86
5.3.3	40-Second Timer	5-87
5.3.3.1	Procurement Specification 40M39536 Function of Hardware	5-87
5.3.3.2	Physical Characteristics	5-87
5.3.4	EDS Timer No. 2	5-88
5.3.4.1	Function of Hardware	5-88

TABLE OF CONTENTS (Continued)

Section	Title	Page
5.4	Instrumentation System	5-89
5.4.1	Telemetry Calibrator Assembly Model II	5-89
5.4.1.1	Function of Hardware	5-90
5.4.1.2	Performance Characteristics	5-90
5.4.2	Telemetry Calibrator Power and Control Unit	5-92
5.4.2.1	Function of Hardware	5-92
5.4.2.2	Performance Characteristics	5-93
5.4.3	Pulse Code Modulation Digital Data Acquisition System, Model 301	5-94
5.4.3.1	Function of Hardware	5-94
5.4.3.2	Performance Characteristics	5-95
5.4.4	Time Division Multiplexer, Model 270	5-97
5.4.4.1	Function of Hardware	5-97
5.4.4.2	Performance Characteristics	5-98
5.4.5	Computer Interface Unit, Model 501	5-99
5.4.5.1	Function of Hardware	5-99
5.4.5.2	Performance Characteristics	5-99
5.4.6	Digital Multiplexer, Model 410	5-100
5.4.6.1	Function of Hardware	5-100
5.4.6.2	Performance Characteristics	5-100
5.4.7	Telemetry RF Assembly Model II (PCM)	5-101
5.4.7.1	Function of Hardware	5-101
5.4.7.2	Performance Characteristics	5-102
5.4.8	Telemetry Oscillator Assembly Model B1	5-103
5.4.8.1	Function of Hardware	5-103
5.4.8.2	Performance Characteristics	5-104
5.4.9	Telemetry RF Assembly Model II (Analog)	5-105
5.4.9.1	Function of Hardware	5-105
5.4.9.2	Performance Characteristics	5-106
5.4.10	Telemetry VSWR Measuring Assembly, Model 225	5-107
5.4.10.1	Function of Hardware	5-107
5.4.10.2	Performance Characteristics	5-108
5.4.11	Telemetry RF Coupler, Model 222	5-109
5.4.11.1	Function of Hardware	5-109
5.4.11.2	Performance Characteristics	5-109
5.4.12	Telemetry Power Divider, Model 221	5-110
5.4.12.1	Function of Hardware	5-110
5.4.12.2	Performance Characteristics	5-110
5.4.13	Telemetry Coaxial Switch	5-111
5.4.13.1	Function of Hardware	5-111
5.4.13.2	Performance Characteristics	5-111
5.4.14	Telemetry RF Dummy Load	5-112
5.4.14.1	Function of Hardware	5-112
5.4.14.2	Performance Characteristics	5-113
5.4.15	Telemetry Antenna Assembly, Model 223	5-113

TABLE OF CONTENTS (Continued)

Section	Title	Page
5.4.15.1	Function of Hardware	5-113
5.4.15.2	Performance Characteristics	5-114
5.4.16	Measuring Rack Selector	5-114
5.4.16.1	Function of Hardware	5-114
5.4.16.2	Performance Characteristics	5-116
5.4.17	Measuring Rack	5-117
5.4.17.1	Function of Hardware	5-117
5.4.17.2	Performance Characteristics	5-117
5.4.18	Measuring Distributors	5-118
5.4.18.1	Function of Hardware	5-118
5.4.18.2	Performance Characteristics	5-120
5.5	Tracking System	5-123
5.5.1	AZUSA Transponder Type C	5-123
5.5.1.1	Function of Hardware	5-123
5.5.1.2	Performance	5-123
5.5.2	AZUSA Radio Interference Filter	5-124
5.5.2.1	Function of Hardware	5-124
5.5.2.2	Performance	5-124
5.5.3	AZUSA Antenna, Model 711	5-124
5.5.3.1	Function of Hardware	5-124
5.5.3.2	Performance	5-124
5.5.4	C-Band Transponder	5-125
5.5.4.1	Function of Hardware	5-125
5.5.4.2	Performance Characteristics	5-125
5.6	Command System	5-127
5.6.1	Command Receiver	5-127
5.6.1.1	Function of Hardware	5-127
5.6.1.2	Performance Characteristics	5-127
5.6.2	Command Decoder	5-129
5.6.2.1	Function of Hardware	5-129
5.6.2.2	Performance Characteristics	5-130
5.6.3	Command Antenna	5-130
5.6.4	Command Power Distributor	5-131
5.6.5	Command Directional Coupler	5-131
5.7	Electrical System	5-133
5.7.1	Power Distributor	5-133
5.7.1.1	Function of Hardware	5-133
5.7.1.2	Performance Characteristics	5-134
5.7.2	Auxiliary Power Distributor	5-135
5.7.2.1	Function of Hardware	5-135
5.7.2.2	Performance Characteristics	5-135
5.7.3	56-Volt Power Supply	5-136
5.7.3.1	Function of Hardware	5-136
5.7.3.2	Performance Characteristics	5-137
5.7.4	5-Volt Master Measuring Supply	5-138

TABLE OF CONTENTS (Continued)

Section	Title	Page
5.7.4.1	Function of Hardware	5-138
5.7.4.2	Performance Characteristics	5-138
5.7.5	Batteries	5-139
5.7.5.1	Function of Hardware	5-139
5.7.5.2	Performance Characteristics	5-140
5.7.6	Network Cables	5-141
5.7.6.1	Function of Hardware	5-141
5.7.6.2	Performance Characteristics	5-141
5.8	Emergency Detection System (EDS)	5-143
5.8.1	EDS Distributor	5-143
5.8.1.1	Function of Hardware	5-143
5.8.1.2	Performance Characteristics	5-144
5.8.2	Control-EDS Rate Gyros	5-144
5.8.2.1	Function of Hardware	5-145
5.8.2.2	Functional Characteristics	5-145
5.8.2.3	Performance Characteristics	5-145
5.9	Environmental Control System	5-149
5.9.1	Gas Bearing Filter	5-149
5.9.1.1	Function of Hardware	5-149
5.9.2	Two-Cubic Foot Sphere	5-150
5.9.2.1	Function of Hardware	5-150
5.9.3	Gas Bearing Heat Exchanger	5-150
5.9.3.1	Function of Hardware	5-150
5.9.4	Gas Bearing Pressure Regulator	5-151
5.9.4.1	Function of Hardware	5-151
5.9.5	50-Cubic Inch Sphere	5-152
5.9.5.1	Function of Hardware	5-152
5.9.6	Solenoid Valve	5-153
5.9.6.1	Function of Hardware	5-153
5.9.7	Mounting and Thermal Conditioning Panel	5-153
5.9.7.1	Function of Hardware	5-153
5.9.8	Coolant Pump	5-154
5.9.8.1	Function of Hardware	5-154
5.9.9	Preflight Heat Exchanger	5-154
5.9.9.1	Function of Hardware	5-154
5.9.10	Water Accumulator	5-155
5.9.10.1	Function of Hardware	5-155
5.9.11	Heat Exchanger Assembly Sublimator	5-155
5.9.11.1	Function of Hardware	5-155
5.9.12	Orifice Regulator Assembly	5-155
5.9.12.1	Function of Hardware	5-156
5.9.13	First Stage Pressure Regulator	5-156
5.9.13.1	Function of Hardware	5-156
5.9.14	Water/Methanol Accumulator	5-157
5.9.14.1	Function of Hardware	5-157

TABLE OF CONTENTS (Continued)

Section	Title	Page
5.9.15	Temperature Control System	5-157
5.9.15.1	Function of Hardware	5-157
5.9.15.1.1	Electronics Controller	5-157
5.9.15.1.2	Thermistor	5-158
5.9.15.1.3	Modulating Flow Control Valve	5-158
5.9.16	Coolant Supplying and Petier Manifold	5-159
5.9.16.1	Function of Hardware	5-159
5.9.17	Air/GN ₂ Purge System	5-159
5.9.17.1	Function of Hardware	5-159
5.10	Structures System	5-161
5.10.1	Segment Assembly No. 1	5-161
5.10.1.1	Description	5-161
5.10.2	Segment Assembly No. 2	5-161
5.10.2.1	Description	5-162
5.10.3	Segment Assembly No. 3	5-162
5.10.3.1	Description	5-162
5.10.4	Umbilical Door Assembly	5-162
5.10.4.1	Description	5-162
5.10.5	Access Door Assembly	5-162
5.10.5.1	Description	5-162
5.10.6	Splice Plates	5-163
5.10.6.1	Description	5-163
5.10.7	Cable Tray Assembly	5-163
5.10.7.1	Description	5-163
5.10.8	Umbilical Plate Assembly	5-163
5.10.8.1	Description	5-163
6	DESIGN CONSIDERATIONS	6-1
6.1	General	6-1
6.2	Reliability	6-1
6.2.1	Redundancy	6-1
6.2.1.1	Triple Modular Redundancy	6-1
6.2.1.2	Dual Redundancy	6-1
6.2.1.3	Pair and Spair Redundancy	6-2
6.2.1.4	Quad Redundancy	6-2
6.2.1.5	Back-up Redundancy	6-2
6.2.1.6	Program Back-up Redundancy	6-2
6.2.2	Reliability Goal Allocations	6-3
6.2.2.1	Criticality Category	6-3
6.2.2.1.1	Criticality Category I	6-3
6.2.2.1.2	Criticality Category II	6-4
6.2.2.1.3	Criticality Category III	6-4
6.3	Human Engineering	6-6
6.3.1	Objective	6-6

TABLE OF CONTENTS (Continued)

Section	Title	Page
6.3.2	Design	6-7
6.3.3	Personnel Activity Flow Analysis	6-7
6.3.4	Personnel Activity Description Sheets	6-7
6.3.5	Test and Evaluation	6-7
6.3.6	Human Reliability	6-8
6.3.7	Documentation	6-8
6.4	Manufacturing	6-8
6.5	Logistics.	6-11
6.5.1	Initiation	6-11
6.5.2	Responsibility	6-11
6.5.2.1	Maintainability.	6-11
6.5.2.2	Maintenance Analysis	6-11
6.5.2.3	Spare Parts Provisioning	6-12
6.5.2.4	Logistics Spares Transportation Plan	6-12
6.5.2.4.1	Contractor Operations 	6-12
6.5.2.4.2	KSC Contractor Operations	6-12
6.5.2.5	Material Control.	6-13
6.6	Transportation.	6-13
6.6.1	Mode	6-13
6.6.2	Conditions	6-13
6.6.3	Special Fixtures	6-13
6.6.3.1	Assembled Instrument Unit Handling Tool	6-13
6.6.3.2	Instrument Unit Transporter	6-14
6.6.3.3	Aft Protective Ring	6-14
6.6.3.4	Forward Protection Ring	6-14
6.7	Technical Publications	6-14
6.7.1	Training	6-15
7	QUALITY AND RELIABILITY ASSURANCE PROVISIONS	7-1
7.1	Quality Assurance Program	7-1
7.1.1	General	7-1
7.1.2	Quality Assurance Surveillance.	7-1
7.1.3	Documentation and Implementation	7-1
7.1.3.1	Documents	7-1
7.1.3.2	Defect Analysis	7-2
7.1.3.3	Change Control	7-2
7.1.3.4	Drawing and Specification Review	7-2
7.1.3.5	Identification.	7-3
7.1.3.6	Audits	7-3
7.1.3.7	Data Systems and Reports.	7-3
7.1.4	Test Equipment Calibrations	7-3
7.1.4.1	General	7-3
7.1.4.2	Tests	7-4
7.1.5	In Process and Receiving Inspection Controls	7-4

TABLE OF CONTENTS (Continued)

Section	Title	Page
7.1.5.1	General	7-4
7.1.5.2	Inspection Controls	7-4
7.1.6	Component Test	7-4
7.1.6.1	General	7-4
7.1.6.2	Acceptance Test	7-5
7.1.7	System Test	7-5
7.1.7.1	General	7-5
7.1.7.2	Test Procedures	7-5
7.1.7.3	System Test Documentation	7-6
7.1.7.3.1	End Item Test Plan	7-6
7.1.7.3.2	End Item Test Procedures	7-6
7.1.7.3.3	Equipment Logs	7-6
7.1.7.3.4	Failure Reports	7-6
7.1.7.3.5	Test Data Recording and Analysis	7-6
7.1.7.3.6	Narrative End Item Report	7-6
7.1.7.4	System Test Operation	7-7
7.2	Reliability Program	7-7
7.2.1	Initiation	7-7
7.2.2	Responsibility	7-7
7.2.3	Subcontractors	7-8
7.2.4	Reliability Predictions	7-8
7.2.5	Failure Mode, Effect, and Criticality Studies	7-8
7.2.6	Maintainability and Elimination of Human-Induced ERPN	7-8
7.2.7	Design Reviews	7-8
7.2.8	Failure Reports and Correction	7-8
7.2.9	Standardization of Design Practices	7-8
7.2.10	Parts and Materials Program	7-9
7.2.11	Equipment Logs	7-9
7.2.12	Testing and Reliability Evaluation	7-9
7.2.13	Documentation	7-9
8	PREPARATION FOR DELIVERY	8-1
8.1	General	8-1
8.2	Delivery Preparation	8-1
8.2.1	Instrument Unit Disassembly and Preparation for Shipment	8-1
9	BIBLIOGRAPHY	9-1
9.1	General	9-1

LIST OF ILLUSTRATIONS

Figure	Title	Page
3.1-1	Saturn IB Configuration	3-2
3.1-2	Instrument Units Physical Location	3-2
3.3-1	Saturn IB/v Instrument Unit	3-5
3.3-2	Saturn IB Instrument Unit Equipment Layout	3-6
3.4-1	Saturn IB Instrument Unit Internal Configuration	3-7
4.1-1	Instrument Unit Block Diagram	4-2
4.2.1-1	Guidance System Block Diagram	4-24
4.2.1-2	Navigation Coordinate Systems	4-25
4.2.1-3	Guidance System Flow Diagram	4-27
4.2.1-4	Nominal X Velocity Error	4-31
4.2.1-5	Nominal Y Velocity Error	4-32
4.2.1-6	Nominal Z Velocity Error	4-33
4.2.1-7	Nominal X Position Error	4-34
4.2.1-8	Nominal Y Position Error	4-35
4.2.1-9	Nominal Z Position Error	4-36
4.2.1-10	X Velocity Error With Quantization	4-38
4.2.1-11	Y Velocity Error With Quantization	4-39
4.2.1-12	Z Velocity Error With Quantization	4-40
4.2.1-13	X Position Error With Quantization	4-41
4.2.1-14	Y Position Error With Quantization	4-42
4.2.1-15	Z Position Error With Quantization	4-43
4.2.1-16	Combined X Velocity Error	4-44
4.2.1-17	Combined Y Velocity Error	4-44
4.2.1-18	Combined Z Velocity Error	4-45
4.2.1-19	Combined X Position Error	4-45
4.2.1-20	Combined Y Position Error	4-46
4.2.1-21	Combined Z Position Error	4-46
4.2.1-22	Nominal X Velocity Error	4-49
4.2.1-23	Nominal Y Velocity Error	4-50
4.2.1-24	Nominal Z Velocity Error	4-51
4.2.1-25	Nominal Total Velocity Error	4-52
4.2.1-26	Nominal X Position Error	4-53
4.2.1-27	Nominal Y Position Error	4-54
4.2.1-28	Nominal Z Position Error	4-55
4.2.1-29	Nominal Total Position Error	4-56
4.2.1-30	Combined X Velocity Error	4-57
4.2.1-31	Combined Y Velocity Error	4-57
4.2.1-32	Combined Z Velocity Error	4-58
4.2.1-33	Combined Total Velocity Error	4-58
4.2.1-34	Combined X Position Error	4-59
4.2.1-35	Combined Y Position Error	4-59
4.2.1-36	Combined Z Position Error	4-60
4.2.1-37	Combined Total Position Error	4-60

LIST OF ILLUSTRATIONS (Continued)

Figure	Title	Page
4.2.1-38	Inertial Subsystem Block Diagram	4-66
4.2.1-39	Gyro Servo Loop Simplified Diagram	4-68
4.2.1-40	Accelerometer Servo Loop Simplified Diagram	4-69
4.2.1-41	Vertical or Leveling Loop Simplified Diagram	4-70
4.2.1-42	ST-124M Azimuth Alignment Loop	4-72
4.2.1-43	Optical Spectrum	4-77
4.2.1-44	Computer Subsystem Flow Diagram	4-79
4.2.2-1	Attitude Control System Block Diagram	4-94
4.2.2-2	Attitude Control System Flow Diagram	4-97
4.2.2-3	Coordinate Frame Orientation	4-104
4.2.3-1	Sequencing System Block Diagram	4-114
4.2.3-2	Sequencing System Flow Diagram	4-117
4.2.4-1	Instrumentation System Block Diagram	4-137
4.2.4-2	Instrumentation System Flow Diagram	4-143
4.2.4-3	Sample VHF Gain Probability Directional Function	4-148
4.2.4-4	P-1 Telemetry Subsystem Block Diagram	4-159
4.2.4-5	P-1 Telemetry Subsystem Flow Diagram	4-161
4.2.4-6	F-1 Telemetry Subsystem Block Diagram	4-183
4.2.4-7	F-1 Telemetry Subsystem Flow Diagram	4-185
4.2.5-1	Tracking System Block Diagram	4-192
4.2.5-2	AZUSA Block Diagram	4-193
4.2.5-3	AZUSA Subsystem Flow Diagram	4-195
4.2.5-4	Required Minimum Antenna Gain Versus Maximum Range	4-198
4.2.5-5	C-Band Transponder Subsystem Block Diagram	4-199
4.2.5-6	C-Band Transponder Subsystem Flow Diagram	4-200
4.2.5-7	Required SST-135C Antenna Gain as a Function of Range	4-203
4.2.6-1	Command System Block Diagram	4-207
4.2.6-2	Command System Flow Diagram	4-213
4.2.7-1	28VDC Power Distribution Block Diagram	4-221
4.2.7-2	Battery Loads Profiles for S-IU-205	4-223
4.2.8-1	Instrument Unit Emergency Detection System Block Diagram	4-232
4.2.8-2	Instrument Unit Emergency Detection System Flow Diagram	4-235
4.2.9-1	Environmental Control System Block Diagram	4-258
4.2.9-2	Environmental Control System Flow Diagram	4-260
4.2.9-3	Gas Bearing Supply Subsystem Block Diagram	4-262
4.2.9-4	Gas Bearing Supply Subsystem Flow Diagram	4-263
4.2.9-5	Thermal Conditioning Subsystem Block Diagram	4-266
4.2.9-6	Thermal Conditioning Subsystem Flow Diagram	4-267
4.2.9-7	Purge Subsystem Block Diagram	4-270
4.2.9-8	Purge Subsystem Flow Diagram	4-271
4.2.10-1	Structural System Block Diagram	4-274
4.2.10-2	Typical Section of Honeycomb Sandwich for Instrument Units	4-275
4.2.10-3	Structural System Pictorial	4-276

LIST OF ILLUSTRATIONS (Continued)

Figure	Title	Page
5.1.1-1	ST-124M Gimbal Configuration	5-4
5.1.1-2	Pendulous Integrating Gyro Accelerometer Diagram	5-9
5.1.2-1	Gimbal Electronics Block Diagram	5-19
5.1.2-2	Accelerometer Electronics Block Diagram	5-20
5.1.5-1	Launch Vehicle Digital Computer Block Diagram	5-33
5.1.5-2	Computer Timing Organization	5-36
5.1.5-3	Memory Word Layout	5-38
5.1.6-1	Launch Vehicle Data Adapter Block Diagram	5-45
5.4.1-1	Measuring Rack Selection Signals	5-116

LIST OF TABLES

Table No.	Title	Page
4.1-1	Environmental Spectra for S-IU-205	4-5
4.2.1-1	Xz Time-Tilt Program	4-63
4.2.1-2	Electrical Interface	4-75
4.2.1-3	Major Guidance Program Modes	4-81
4.2.1-4	Guidance Modes	4-83
4.2.1-5	Reasonableness Test Parameters	4-87
4.2.2-1	S-IB Attitude Control System Interface	4-109
4.2.3-1	Switch Selector Register Bit	4-119
4.2.3-2	Output Drive Capability	4-121
4.2.4-1	Rack Selector Command Signal Decoding	4-151
4.2.4-2	Mode Selector Command Signal Encoding	4-151
4.2.4-3	Channel Selector Command Signal Encoding	4-152
4.2.4-4	Remote Automatic Calibration System Accuracy	4-153
4.2.4-5	Transducer Error and Bandwidth in P-1 Telemetry Subsystem	4-166
4.2.4-6	Electrical Pickoff Error and Bandwidth in P-1 Telemetry Subsystem	4-168
4.2.4-7	Transducer Error and Bandwidth in F-1 Telemetry Subsystem	4-188
4.2.4-8	Electrical Pickoff Error and Bandwidth in F-1 Telemetry Subsystem	4-188
5.1.1-1	Gyro Characteristics	5-10
5.1.1-2	Accelerometer Characteristics	5-11
5.1.1-3	Gas Bearing Pendulum Characteristics	5-13
5.1.1-4	Attitude Sensing Resolver Characteristics	5-15
5.1.1-5	Resolver Chain System Characteristics	5-16

LIST OF TABLES (Continued)

Table No.	Title	Page
5.1.5-1	Launch Vehicle TRM Computer Characteristics	5-28
5.1.5-2	Input to LVDC	5-32
5.1.5-3	Output From LVDC	5-32
5.1.6-1	PIO Addresses	5-47
5.1.6-2	Analog-to-Digital Conversion Error Indications	5-50
5.1.6-3	Composition of Telemetry Words as They Appear in Telemetry Storage	5-54
5.1.6-4	Digital Input Signal Characteristics	5-56
5.1.6-5	Drive Capability of Discrete Output Circuits	5-57
5.1.6-6	Interface Signals to RCA-110 Ground Launch Computer	5-57
5.1.6-7	Signal Characteristics	5-61
5.1.6-8	Input Power and Power Distribution	5-65
6.7-1	Technical Publications Schedule	6-14

LIST OF ABBREVIATIONS

- A -

AFC	Automatic Frequency Control
APC	Automatic Pulse Control
APS	Auxiliary Propulsion System
ASC	Accelerometer Signal Conditioner
AVP	Address Verification Pulse

- B -

BTC	Begin Telemetry Cycle
-----	-----------------------

- C -

C-EDS RG	Control -EDS Rate Gyros
CDL	Contractual Document List
CIU	Computer Interface Unit
COD	Cross-over Detector
CRP	Computer Reset Pulse
CSP	Control Signal Processor

- D -

DCS	Digital Command System
DIM	Digital Input Multiplexer
DO	Discrete Output
DIM	Discrete Input
GOR	Discrete Output Register

- E -

EDS	Emergency Detection System
EC	Expected Change
ESE	Environmental Support Equipment
ETC	End of Telemetry Cycle

- F -

FCC	Flight Control Computer
F/M	Thrust/Mass

- G -

GFE	Government Furnished Equipment
GLCC	Ground Launch Control Computer
GRR	Guidance Reference Release
GRRA	Guidance Reference Release Abort

- I -

IGM	Iterative Guidance Mode
ICR	Internal Control Register
I&T	Instrumentation and Telemetry
INTR	Interrupt
IR	Interrupt Register
IU	Instrument Unit

- L -

LIRO	Load In Readout
LLS	Low Level Sense
LVDA	Launch Vehicle Data Adapter
LVDC	Launch Vehicle Digital Computer

- M -

MA	
MAP	Message Acceptance Pulse
MCC	Mission Control Center
MCP	Management Control Parameter
MF	Medium Frequency
MSFC	Marshall Space Flight Center
MSFN	Manned Space Flight Network

- O -

OECO	Outboard Engine Cutoff
OM/D	Orbit Mode Data Bits
ORBNAV	Orbital Navigation Computer Program

- P -

PIO	Process Input Output
PMR	Pacific Missile Range
PSK	Phase Shift Key
PTL	Prepare To Launch

- Q -

QCI	Quality Control Instructions
-----	------------------------------

- R -

RACS	Remote Automatic Calibration System
RTC	Reasonableness Test Constant

- S -

SCO	Subcarrier Oscillator
SSCO	Switch Selector Channel Output
SSR	Switch Selector Register
STO	Stored Memory

- T -

TB0	Time Base Zero
TM1	Transfer Minus One
TMZ	Transfer (LVDC Instruction)
TMR	Triple Modular Redundant
TRA	Unconditional <u>TRAnsfer</u>

4BCO	S-IVB Engine Cutoff
------	---------------------

SECTION 1

SCOPE

1.1 PURPOSE

A model specification for the Instrument Unit (IU) shall be prepared and maintained. The specification shall provide a summary description of the stage, interrelated subsystems, and major elements in detail sufficient to establish that design. Performance, human factors, and reliability are compatible with operational requirements that are established by the procuring activity.

1.2 OBJECTIVE

The following are the objectives for the use of the Instrument Unit model specification:

- A. The model specification shall define an IU base line capable of being assessed and evaluated against a particular set of Marshall Space Flight Center mission requirements to determine a compatible IU configuration.
- B. The model specification shall define the design configuration base lines of the IU to be delivered.
- C. The model specification shall define the plans and procedures for the implementation (manufacture, quality assurance, and support) of the IU design.
- D. The model specification shall delineate system criteria essential to generation of an IU test specification.
- E. This specification shall establish a means of IBM/MSFC configuration control (including changes) and product improvement.
- F. The model specification shall describe known configuration compliance to those factors referred to as "design considerations" in MSFC document CD-214-506, Revision A, dated: 1 October 1964.

1.3 AUTHORITY

The authority for this specification is as defined by the Marshall Space Flight Center (MSFC) under contract NAS8-14000. The basic requirement for a model specification is defined in MSFC-STD-263A, dated 18 December 1963, entitled "Data Submittal", Section 5.1.1.

1.4 PERFORMANCE

The systems performance data generated herein is the product of studies and analyses performed by the Federal Systems Division of the International Business Machines Corporation under MSFC contract NAS8-14000. These data are based on accumulated MSFC or IBM Instrument Unit component procurement specifications and/or all other available performance information of decreasing authority transmitted under contract NAS8-14000. All data on Government Furnished Equipment (GFE) has been furnished by MSFC. At specific parametric data points, reference has been made to "systems engineering" documentation generated in the analysis of MSFC data. A complete bibliography of such supporting documents is contained in Section 9.

SECTION 2

APPLICABLE DOCUMENTS

2.1 SPECIFICATIONS, STANDARDS, AND PROCESSES

The specifications, standards, and processes listed in the IBM Contractual Document List (CDL) are the applicable documents required to define the engineering end item requirements of the Instrument Unit.

The CDL for Instrument Unit, Apollo-Saturn 205 (AS-205) shall be IBM document number 65-237 _____ H.

The CDL shall list the specification exceptions approved against the individual applicable document. These documents, of the listed revision or issue date, form a part of this specification to the extent specified in this specification. If there is conflict between reference documents and the content of this specification, the content of this specification shall take precedence.

SECTION 3

CONFIGURATION

3.1 STAGE FUNCTION

The Saturn IB is a multistage booster vehicle used in performing scientific space missions. The Instrument Unit is a nonpropulsive instrumentation stage of the Saturn IB. The Instrument Unit for the AS-205 mission is herein related to the remainder of the AS-205 vehicle.

The Instrument Unit for the Saturn IB vehicle may be considered as the third stage of a four-stage vehicle consisting of the following:

- A. S-IB lower stage booster
- B. S-IVB second stage
- C. Instrument Unit
- D. Spacecraft or payload

Figure 3.1-1 shows the Saturn IB configuration with stations and dimensions indicated. Figure 3.1-2 shows the Instrument Unit's physical location in the Saturn IB vehicle.

3.2 GENERAL DESCRIPTION

The Instrument Unit for the Saturn IB vehicle shall be a distinct section capable of being assembled to the other sections of the vehicle at specific field splices. The Instrument Unit contains the equipment necessary to perform guidance and control of the overall boost vehicle, vehicle instrumentation necessary for performance and evaluation, radar tracking aids and command guidance functions. An Environmental Control System, an Electrical System, and a Structural System shall be provided as support equipment.

3.3 EXTERNAL CONFIGURATION

The Instrument Unit structure shall be capable of being mated, by field splice, to the S-IVB Stage and the Apollo adapter. Vehicle structural loads between the Apollo spacecraft and the S-IVB stage shall be transmitted by the Instrument Unit.

All external interface connections to prelaunch equipments shall be made through separable umbilical connections. All connections to the Apollo Spacecraft and the S-IVB stages shall be permanent at the Instrumental Unit interface.




Figure 3.1-1 Saturn IB Configuration




Figure 3.1-2 Instrument Units Physical Location

When the vehicle has been assembled, access to internal systems of the Instrument Unit shall be provided through a skin access door. The external profile of the Instrument Unit shall be as shown in Figures 3.3-1 and 3.3-2. The Instrument Unit shall be of cylindrical shape, 260 inches in diameter and 36 inches in mated height and will be located between stations 1663 and 1699 of the vehicle, whose overall height is approximately 2720 inches as shown in Figure 3.1-1.

The profile height of the Instrument Unit shall be increased by 12.5 inches when the cable tray assemblies are installed.

The profile diameter of the Instrument Unit shall be increased by the various antennae mounted on the exterior of the Instrument Unit.

The external surface of the AS-205 Instrument Unit shall be painted black. Position numbers, fin locations, decks, and other identification data shall be in accordance with drawing 30Z13100; Instrument Unit Assembly.

3.4 INTERNAL CONFIGURATION

The internal configuration of the Instrument Unit is shown in Figure 3.4-1. The figure shows the equipment shall be mounted around the inside surface of the cylinder where the arc-segments are drawn in flat projection. Orientation of equipments shall be such as to maximize function, minimize interference characteristics, and distribute weight and thermal dissipation loads.

Internal surfaces of the Instrument Unit shall be painted with number 625 aluminum (Thermocote) color in accordance with MSFC, ASTR.: Guide Lines Brief Vol. III, No. 3A, in order to reduce surface emissivity of components to 0.4 or less. Preparations and procedures for applying the finish are specified in IBM Specification No. 7907352.

3.5 MASS CHARACTERISTICS

The dry weight of the fully configured S-IU-205 shall be no more than 3657 ± 100 pounds. Charged weight shall be 3931 ± 100 pounds. The actual weights and balance shall be reported in accordance with MSFC Document No. III-4-413-13, (IBM-65-214-0010H).

Disposition of the mass of the instrumentation contained within the Instrument Unit shall be around the inner periphery of the cylinder. The open area in the center shall be capable of accommodating the top of the S-IVB hydrogen dome, and the legs of the LEM.

3.6 INTERFACE CONTROL

Mechanical integration of the S-IU-205 with the S-IVB and with Apollo payloads is controlled by interface control documents 13M20507 and 13M20508 for the S-IB vehicle.




Figure 3.3-1 Saturn IB/N Instrument Unit




Figure 3.3-2 Saturn IB Instrument Unit Equipment Layout




Figure 3.4-1 Saturn IB Instrument Unit Internal Configuration

Electrical interfaces are described in the sections pertaining to those specific functions. In addition, the following interface control drawings shall apply:

INTERFACE CONTROL DOCUMENTS (S-IU-205)

40M30695	Definition of Saturn IB Vehicle S-IVB/IV Electrical Interface
40M35007	Definition of Saturn IB Vehicle IV/ESE Electrical Interface

Instrument Unit to Launch GSE

13M20505	Physical Requirements
13M06465	Functional Requirements
13M04465	Environmental Requirements
13M02465	Procedural Requirements
13M00465	Human Factors Requirements

S-IVB to Instrument Unit

13M20507	Physical Requirements
13M06467	Functional Requirements
13M04467	Environmental Requirements
13M02467	Procedural Requirements
13M00467	Human Factors Requirements

Instrument Unit to Spacecraft

13M20508	Physical Requirements
13M06468	Functional Requirements
13M04468	Environmental Requirements
13M02468	Procedural Requirements
13M00468	Human Factors Requirements
13M20517	Envelope LEM/S-IVB/IV Clearance
40M37509	Definition of Saturn SA-205 and Apollo SC-014 Electrical Interface