

Payload Powerdown


STS-129

**Mission Operations Directorate
Operations Division**

**Final
October 22, 2009**

National Aeronautics and
Space Administration

Lyndon B. Johnson Space Center
Houston, Texas




JSC-48097-129

MISSION OPERATIONS DIRECTORATE


**PAYLOAD POWERDOWN
STS-129**

FINAL
October 22, 2009

PREPARED BY:



Yvette L. Dillard
Publication Manager

APPROVED BY:



Manager,
Flight Procedures

ACCEPTED BY:



Michael T. Hurt
FDF Manager

This document is under the configuration control of the Crew Procedures Control Board (CPCB). All proposed changes must be submitted via Change Request Workflow (CRW) to DO3/FDF Manager.

Additional distribution of this book, for official use only, may be requested in writing to DO3/PMO Administrator. The request must include justification and requester's name, organization, position, and phone number. Contractor requests are made through the NASA or DOD organization supported. Deletions, reduction in quantity, or change of address may be submitted to DO3/FDF Management Office, 281-244-1184.

PL PWR/129/FIN

Incorporates the following:
482#: PL PWR-00149 PL PWR-00150B

AREAS OF TECHNICAL RESPONSIBILITY

Publication Manager	DO35/Y. Dillard	281-244-1174
Alternate Publication Manager	DO35/L. Giles	281-244-9068
ORB PWRDNS	DS43/C. Sweitzer	281-483-6355
PL PWRDN	DO5/T. Batten	281-244-0201

NOTES

1. Section 1 of this book is inserted at the back of the Ascent Pocket Checklist.
2. Sections 2 and 3 of this book are inserted at the back of the Orbit Pocket Checklist.
3. Section 4 of this book is inserted at the back of the Entry Pocket Checklist.

PAYLOAD POWERDOWN
STS-129

LIST OF EFFECTIVE PAGES

FINAL 10/22/09

Sign Off	*	129/FIN
PL ii	*	129/FIN
PL iii	*	129/FIN
PL iv	*	129/FIN
PL v	*	129/FIN
PL vi	*	129/FIN
PL 1-1.....		129/A/FIN
PL 1-2.....		129/A/FIN
PL 1-3.....		129/A/FIN
PL 1-4.....		129/A/FIN
PL 2-1.....		129/O/FIN
PL 2-2.....		129/O/FIN
PL 2-3.....		129/O/FIN
PL 2-4.....		129/O/FIN
PL 2-5.....		129/O/FIN
PL 2-6.....		129/O/FIN
PL 2-7.....		129/O/FIN
PL 2-8.....		129/O/FIN
PL 3-1.....		129/O/FIN
PL 3-2.....		129/O/FIN
PL 3-3.....		129/O/FIN
PL 3-4.....		129/O/FIN
PL 4-1.....		129/E/FIN
PL 4-2.....		129/E/FIN
PL 4-3.....		129/E/FIN
PL 4-4.....		129/E/FIN

* – Omit from flight book

PL iii

PL PWR/129/FIN

This Page Intentionally Blank

PL iv

PL PWR/129/FIN

<u>CONTENTS</u>	<u>PAGE</u>
<u>PL PWRDN – ASCENT</u>	PL 1-1
PL PWRDN MATRIX.....	PL 1-2
ACTION.....	PL 1-2
PWRDN A.....	PL 1-2
MIDDECK PAYLOADS	PL 1-2
ABRS.....	PL 1-3
CGBA	PL 1-3
PWRDN B.....	PL 1-3
MIDDECK REAR-BREATHER PAYLOADS	PL 1-3
ABRS.....	PL 1-3
<u>PL PWRDN – ORBIT</u>	PL 2-1
PL PWRDN MATRIX.....	PL 2-2
ACTION.....	PL 2-3
PRIORITY PWRDN PP3A.....	PL 2-3
PCS.....	PL 2-3
OIU.....	PL 2-3
PRIORITY PWRDN PP3B	PL 2-4
MIDDECK PAYLOADS	PL 2-4
ABRS (if powered).....	PL 2-4
CGBA	PL 2-4
GLACIER (if powered).....	PL 2-4
MDS (if powered).....	PL 2-5
OBSS	PL 2-5
SASA.....	PL 2-5
ELC1 & 2.....	PL 2-5
PL BUS DEACT	PL 2-5
PWRDN A.....	PL 2-6
ORBITER	PL 2-6
PWRDN B.....	PL 2-6
PWRDN C.....	PL 2-7
MIDDECK REAR-BREATHER PAYLOADS	PL 2-7
ABRS (if powered).....	PL 2-7
MDS (if powered).....	PL 2-7
GLACIER (if powered).....	PL 2-7
ABRS (if previously powered).....	PL 2-7
MDS (if previously powered)	PL 2-7
GLACIER (if previously powered).....	PL 2-8

<u>PL SAFING – ORBIT</u>	PL 3-1
PL SAFING MATRIX	PL 3-2
ACTION.....	PL 3-3
PL SAFING	PL 3-3
MIDDECK TRANSFER	
(IF NOT ALREADY PERFORMED)	PL 3-3
MIDDECK PAYLOADS	PL 3-3
ABRS/MDS (if powered).....	PL 3-3
GLACIER (if powered).....	PL 3-3
CGBA	PL 3-3
OIU.....	PL 3-3
APCU	PL 3-3
SPINAL ELONGATION.....	PL 3-4
PAYLOAD BUSES	PL 3-4
 <u>PL PWRDN – ENTRY</u>	PL 4-1
PL PWRDN MATRIX.....	PL 4-2
ACTION.....	PL 4-2
PWRDN A.....	PL 4-2
MIDDECK PAYLOADS	PL 4-2
MDS.....	PL 4-2
GLACIER.....	PL 4-2
CGBA	PL 4-2
PWRDN B.....	PL 4-3
MIDDECK REAR-BREATHER PAYLOADS	PL 4-3
MDS.....	PL 4-3
GLACIER.....	PL 4-3

PL PWRDN – ASCENT

PL PWRDN MATRIX.....	PL 1-2
ACTION.....	PL 1-2
PWRDN A	PL 1-2
MIDDECK PAYLOADS.....	PL 1-2
ABRS	PL 1-3
CGBA.....	PL 1-3
PWRDN B	PL 1-3
MIDDECK REAR-BREATHER PAYLOADS	PL 1-3
ABRS	PL 1-3

PL PWRDN
ASC

129

PL 1-1

PL PWR/129/A/FIN

**PL PWRDN
ASC**

PL PWRDN MATRIX

PROCEDURE	ACTION
PWRDN FOR LOSS OF:	
2 CAB FANS	A
CAB PRESS	
(MINOR PWRDN; from step 4)	A
(MAJOR PWRDN; from step 5)	A
AV BAY COOLING/AV BAY FIRE	B
2 H2O LOOPS	
[PLT PWRDN, SYS AOA, <u>2 H2O LOOPS (AOA);</u> (CDR/PLT PWRDNS)]	A
(POST OMS-2)	A
1 FREON LOOP	N/A
2 FREON LOOPS	
[PLT PWRDN, SYS AOA, <u>2 FREON LOOPS (AOA);</u> (CDR/PLT PWRDNS)]	A
(POST OMS-2)	A
HI LOAD EVAP	N/A
FES /1 FC	N/A
2nd FC	A
MN BUS UNDERVOLTS/FC VOLTS	
(from step 6; permanent loss of PL PRI)	N/A
(from step 14; temporary loss of PL PRI)	N/A

ACTION

A	PWRDN	PWRUP
<u>MIDDECK PAYLOADS</u>		N/A
<u>NOTE</u> When orbiter power removed, science degradation or loss will occur to ABRS (30 min), CGBA (30 min)		

129

PL 1-2

PL PWR/129/A/FIN

A (Cont)	PWRDN	PWRUP
	<u>ABRS</u> MF28E 1. cb POWER – op ML85E 2. DC 10 AMP MNB S4 – OFF cb DC 10 AMP MNB CB4 – op	
	<u>CGBA</u> MF71E 3. cb MAIN POWER – op MO63P 4. 10A J4 – OFF 5. cb CB4/J4 – op	

B	PWRDN	PWRUP
	<u>MIDDECK REAR-BREATHER PAYLOADS</u>	N/A
	<u>NOTE</u> When orbiter power removed, science degradation or loss will occur to ABRS (30 min)	
	IF AV BAY 1: <u>ABRS</u> MF28E 1. cb POWER – op ML85E 2. DC 10 AMP MNB S4 – OFF cb DC 10 AMP MNB CB4 – op	

129

PL 1-3

PL PWR/129/A/FIN

This Page Intentionally Blank

129

PL 1-4

PL PWR/129/A/FIN

PL PWRDN – ORBIT

PL PWRDN MATRIX.....	PL 2-2
ACTION.....	PL 2-3
PRIORITY PWRDN PP3A.....	PL 2-3
PCS	PL 2-3
OIU	PL 2-3
PRIORITY PWRDN PP3B.....	PL 2-4
MIDDECK PAYLOADS.....	PL 2-4
ABRS (if powered)	PL 2-4
CGBA.....	PL 2-4
GLACIER (if powered)	PL 2-4
MDS (if powered)	PL 2-5
OBSS	PL 2-5
SASA	PL 2-5
ELC1 & 2	PL 2-5
PL BUS DEACT.....	PL 2-5
PWRDN A	PL 2-6
ORBITER.....	PL 2-6
PWRDN B	PL 2-6
PWRDN C	PL 2-7
MIDDECK REAR-BREATHER PAYLOADS	PL 2-7
ABRS (if powered)	PL 2-7
MDS (if powered)	PL 2-7
GLACIER (if powered)	PL 2-7
ABRS (if previously powered)	PL 2-7
MDS (if previously powered)	PL 2-7
GLACIER (if previously powered)	PL 2-8

**PL PWRDN
ORB**

PL PWRDN MATRIX

PROCEDURE	ACTION
PWRDN FOR LOSS OF:	
HI LOAD EVAP	N/A
1 FREON LOOP	PP3A*,PP3B** (on MCC call) as required
AV BAY COOLING (from MAL GPC FRP-7)	C
1 FC	PP3A*, PP3B** (on MCC call) as required until ORB kW < 17
FES (ON ORBIT)	PP3A*,PP3B** (on MCC call) as required
(DEORBIT PREP)	A
MN BUS UNDERVOLTS/FC VOLTS (from step 6; permanent loss of PL PRI)	B
(from step 17; temporary loss of PL PRI)	B
AV BAY FIRE	C
PRIORITY PWRDN GROUP 3	PP3A*,PP3B** (on MCC call) as required

*PRIORITY PWRDN 3A (PP3A) contains recoverable Payload Operations Powerdown steps

**PRIORITY PWRDN 3B (PP3B) is a total Payload Powerdown that may cause Payload Operations to be nonrecoverable

ACTION

PP3A	PRIORITY PWRDN (Recoverable) (On MCC call only)	PWRUP
<u>PCS</u> L12(PDIP 1)	1. Exit programs, power off PCS 2. DC PWR 1 – OFF	√MCC
<u>OIU</u> L12U (SSP1)	3. OIU PWR – OFF (tb-bp)	
If additional powerdown required:	4. Go to PRIORITY PWRDN 3B (PP3B)	

129

PL 2-3

PL PWR/129/O/FIN

PP3B	PRIORITY PWRDN (Non-Recoverable) (On MCC call only)	PWRUP
<u>MIDDECK PAYLOADS</u>	<p><u>NOTE</u></p> <p>When orbiter power removed, science degradation or loss will occur to ABRS (30 min), GLACIER (120 min @ -95C), MDS (15 min), CGBA (30 min)</p> <p><u>ABRS</u> (if powered)</p> <p>MF28E 1. cb POWER – op</p> <p>ML85E 2. DC 10 AMP MNB S4 – OFF 3. cb DC 10 AMP MNB CB4 – op</p> <p><u>CGBA</u></p> <p>MF71E 4. pb MENU → Press 5. pb 7 Shutdown → Press 6. pb ENTER → Press 7. pb 1 Shutdown System → Press 8. pb ENTER → Press 9. √Display OK TO POWERDOWN 10. cb MAIN POWER – op</p> <p>MO63P 11. 10A J4 – OFF 12. cb CB4/J4 – op</p> <p><u>GLACIER</u> (if powered)</p> <p>MA16F/G 13. pb Left (MENU) → Press (one time) QUICK STATUS 1/5 14. pb Left (NEXT) → Press (four time) SHUTDOWN 5/5 15. pb Center (SELECT) → Press (one time) SHUTDOWN 1/2 16. pb Center (SELECT) → Press (one time) Confirm Shutdown 17. pb Left (APPLY) → Press (one time) Shutting Down Please Wait 18. √Display Shutdown Complete TURN POWER OFF 19. √BATTERY – ON (It on) 20. cb POWER – op (It off) 21. cb MNB MAR 1 – op</p>	N/A

PP3B (Cont)	PRIORITY PWRDN (Non-Recoverable) (On MCC call only)	PWRUP
	<u>MDS</u> (if powered)	
MF28E/G	22. cb POWER cb – OPEN (all lts off)	
ML85E	23. DC 10 AMP MNB S4 – OFF	
	24. cb DC 10 AMP MNB CB4 – op	
	<u>OBSS</u>	
	25. LCC DEACT (Cue Card, <u>LCS</u>)	
	26. LCH DEACT (Cue Card, <u>LCS</u>)	
	27. LDRI/ITVC DEACT (Cue Card, <u>LDRI/ITVC</u>)	
	<u>SASA</u>	
R1	28. PL AFT MNC – OFF	
	<u>ELC1 & 2</u>	
R1	29. PL PRI MNC – OFF (tb-OFF)	
	<u>PL BUS DEACT</u>	
R1	30. PL CAB – OFF	
	31. AUX – OFF	

129

PL 2-5

PL PWR/129/O/FIN

A	PWRDN (to reduce internal cabin heat loads)	PWRUP
<u>ORBITER</u>	Exit software programs, power down all non-essential PGSCs and orbiter equipment (OCAC, Ergometer,Battery Chargers, etc)	√MCC

B	PWRDN (PL PRI permanently or temporarily lost)	PWRUP
L12 (SSP1)	√APCU 1,2 CONV (two) – OFF √OUTPUT RLY (two) – OP	√MCC

129

PL 2-6

PL PWR/129/O/FIN

C	PWRDN	PWRUP
	<u>MIDDECK REAR-BREATHER PAYLOADS</u>	✓MCC
	<u>NOTE</u> When orbiter power removed, science degradation or loss will occur to ABRS (30 min), MDS (15 min), GLACIER (120 min @ -95C)	
	IF AV BAY 1: MF28E <u>ABRS</u> (if powered) 1. cb POWER – op ML85E 2. DC 10 AMP MNB S4 – OFF 3. cb DC 10 AMP MNB CB4 – op MF28E/G <u>MDS</u> (if powered) 4. cb POWER cb – OPEN (all its off) ML85E 5. DC 10 AMP MNB S4 – OFF 6. cb DC 10 AMP MNB CB4 – op	
	IF AV BAY 3: MA16F/G <u>GLACIER</u> (if powered) 7. ✓BATTERY – ON (It on) 8. cb POWER – op (It off) ML86B:E 9. cb MNB MAR 1 – op	
	PWRUP	
	On MCC GO: IF AV BAY 1: MF28E <u>ABRS</u> (if previously powered) 1. ✓sw POWER – ON 2. cb POWER – cl ML85E 3. cb DC 10 AMP MNB CB4 – cl 4. sw DC 10 AMP MNB S4 – ON ML85E <u>MDS</u> (if previously powered) 5. cb DC 10 AMP MNB CB4 – cl 6. DC 10 AMP MNB S4 – ON MF28E/G 7. cb POWER cb – CLOSED ✓MDS POWER LED – On ✓PRIMARY POWER LED – On ✓MODE & STATUS LED – Off	

C (Cont)	PWRUP
IF AV BAY 3:	
ML86B:E	<u>GLACIER</u> (if previously powered) 8. cb MNB MAR 1 – cl
MA16F/G	9. cb POWER – cl (It on) 10. √BATTERY – ON (It on)

129

PL 2-8

PL PWR/129/O/FIN

PL SAFING – ORBIT

PL SAFING MATRIX.....	PL 3-2
ACTION.....	PL 3-3
PL SAFING.....	PL 3-3
MIDDECK TRANSFER	
(IF NOT ALREADY PERFORMED)	PL 3-3
MIDDECK PAYLOADS.....	PL 3-3
ABRS/MDS (if powered)	PL 3-3
GLACIER (if powered)	PL 3-3
CGBA.....	PL 3-3
OIU	PL 3-3
APCU.....	PL 3-3
SPINAL ELONGATION	PL 3-4
PAYLOAD BUSES.....	PL 3-4

PL SAFING
ORB

129

PL 3-1

PL PWR/129/O/FIN

PL SAFING MATRIX

PROCEDURE	ACTION
9.101 JOINT EXPEDITED UNDOCKING AND SEPARATION, from step 18b (SODF: JOINT OPS, <u>EMERGENCY RESPONSE</u> ; JEUS)	PL SAFING
PWRDN FOR LOSS OF:	
2 CAB FANS	PL SAFING
2 H2O LOOPS	PL SAFING
CAB PRESS	PL SAFING
(2nd FC (TIG < 4 hr) (from step 5))	PL SAFING
(TIG > 4 hr) (from step 15)	PL SAFING
2 FREON LOOPS	PL SAFING

PL SAFING
ORB

129

PL 3-2

PL PWR/129/O/FIN

ACTION

PL SAFING	
<u>MIDDECK TRANSFER (IF NOT ALREADY PERFORMED)</u>	
If transfer hardware in ODS: 1. Complete transfer to ISS Else: 2. Stow in Middeck	
<u>MIDDECK PAYLOADS</u>	
<u>ABRS/MDS</u> (if powered) ML85E 3. DC 10 AMP MNB S4 – OFF 4. cb DC 10 AMP MNB CB4 – op	
<u>GLACIER</u> (if powered) ML86B:E 5. cb MNB MAR 1 – op	
MA16F/G If Glacier Door Captive Locks (two) are unlocked perform: MF28K 6. Unstow Tools 3/16" Hex Head, 3/8" Drive 1/4" to 3/8" Adapter 4" Ext, 1/4" Drive (40-200 in-lbs) Trq Wrench, 1/4" Drive	
MA16F/G 7. ✓Door Latch – Locked (Finger latches fully spread apart and locking flap positioned between finger latches) 8. Fasten Glacier Door Captive Locks (two), torque to 75 in-lbs using to Trq Wrench	
MF28K 9. Stow tools	
<u>CGBA</u> MO63P 10. 10A J4 – OFF 11. cb CB4/J4 – op	
<u>OIU</u> L12U 12. OIU PWR – OFF (tb-bp) (SSP1)	
<u>APCU</u> L12U 13. ✓APCU 1,2 CONV (two) – OFF (tb-bp) (SSP1) ✓OUTPUT RLY (two) – OP (tb-bp)	

129

PL 3-3

PL PWR/129/O/FIN

PL SAFING (Cont)

SPINAL ELONGATION

If Spinal Elongation ops in progress:

14. Remove Spinal Elongation hardware from CDR Seat
15. Re-install Head Rest and Seat Cushion to nominal config
16. Return Shoulder harness and lap belt to nominal config
17. Remove D2X Camera and Multi-use arm, stow

If ISS hatch still open:

18. Return Spinal Elongation hardware to ISS

Else:

19. Stow Spinal Elongation hardware on Shuttle

PAYLOAD BUSES

20. PL PRI MNC – OFF (tb-OFF)
21. √MNB,FC3 (two) – ctr (tb-OFF)
22. AUX – OFF
23. CAB – OFF
24. √AFT MNB – OFF
25. MNC – OFF

Once PL SAFING completed, return to calling procedure, if required

Once calling procedure completed, stow all non-essential orbiter equipment (OCAC,Cycle Ergometer,Battery Chargers, etc)

129

PL 3-4

PL PWR/129/O/FIN

PL PWRDN – ENTRY

PL PWRDN MATRIX.....	PL 4-2
ACTION.....	PL 4-2
PWRDN A	PL 4-2
MIDDECK PAYLOADS.....	PL 4-2
MDS	PL 4-2
GLACIER	PL 4-2
CGBA.....	PL 4-2
PWRDN B	PL 4-3
MIDDECK REAR-BREATHER PAYLOADS	PL 4-3
MDS	PL 4-3
GLACIER	PL 4-3

PL PWRDN
ENT

129

PL 4-1

PL PWR/129/E/FIN

PL PWRDN MATRIX

PROCEDURE	ACTION
PWRDN FOR LOSS OF:	
2 CAB FANS	A
2 H2O LOOPS (ENTRY)	A
CAB PRESS	A
AV BAY COOLING (ENTRY)	B
1 FREON LOOP/HI LOAD EVAP (ENTRY)	N/A
FES	N/A
1 FC (ENTRY)	N/A
2 FREON LOOPS (ENTRY)	A
2nd FC (ENTRY)	A
MN BUS UNDERVOLTS/FC VOLTS (from step 6; permanent loss of PL PRI) (from step 14; temporary loss of PL PRI)	N/A N/A

ACTION

A	PWRDN	PWRUP
<u>MIDDECK PAYLOADS</u>		N/A
	<u>NOTE</u> When orbiter power removed, science degradation or loss will occur to MDS (15 min), GLACIER (120 min @ -95 C), CGBA (30 min)	
MF28E/G	<u>MDS</u> 1. cb POWER cb – OPEN (all lts off)	
ML85E	2. DC 10 AMP MNB S4 – OFF 3. cb DC 10 AMP MNB CB4 – op	
MA16F/G	<u>GLACIER</u> 4. √BATTERY – ON (lt on) 5. cb POWER – op (lt off)	
ML86B:E	6. cb MNB MAR 1 – op	
MF71E	<u>CGBA</u> 7. cb MAIN POWER – op	
MO63P	8. 10A J4 – OFF 9. cb CB4/J4 – op	

PL PWRDN
ENT

129

PL 4-2

PL PWR/129/E/FIN

B	PWRDN	PWRUP
	<u>MIDDECK REAR-BREATHER PAYLOADS</u> <p style="text-align: center;"><u>NOTE</u></p> <p>When orbiter power removed, science degradation or loss will occur to MDS (15 min), GLACIER (120 min @ -95 C)</p> <p>IF AV BAY 1:</p> <p style="text-align: center;"><u>MDS</u></p> <p>MF28E/G 1. cb POWER cb – OPEN (all lts off) ML85E 2. DC 10 AMP MNB S4 – OFF 3. cb DC 10 AMP MNB CB4 – op</p> <p>IF AV BAY 3:</p> <p style="text-align: center;"><u>GLACIER</u></p> <p>MA16F/G 4. √BATTERY – ON (lt on) 5. cb POWER – op (lt off) ML86B:E 6. cb MNB MAR 1 – op</p>	N/A

129

PL 4-3

PL PWR/129/E/FIN

This Page Intentionally Blank

129

PL 4-4

PL PWR/129/E/FIN

Space Shuttle Program
FLIGHT DATA FILE

JSC-48097-129
FINAL



**PAYLOAD
POWERDOWN**

**STS
129**

Flight Cover (trim bottom to expose tabs)